



Timney® Weatherby Mark V Trigger Installation Instructions

Please read these instructions before you install your new Timney® trigger

1. **Unload the rifle, making sure the chamber and the magazine are empty.** Remove the bolt. Remove the screws that hold the action to the stock, now remove action from the stock.

if it does; either the pull weight has been to low (1.5 lb. min.) or it may need additional sear engagement.

2. Remove the factory trigger from the action:

1. The American model has 2 mounting screws (A & C) holding it in place, keep these screws handy as you will need them to install your Timney trigger.

2. The German model has 1 mounting screw (A) and a mounting pin (B) holding it in place, keep these handy as you will need them to install your Timney trigger.

3. Attach the Timney® trigger to the action with the screw(s) and pin (German model) so that it is snug and the assembly does not move around on the receiver.

4. Re-install the action in the stock. Now go ahead and test the trigger by dry firing it a couple of times.

5. Another test you can do is to cock the rifle and drop it butt first about 6-8" to the floor to insure it does not slam fire.

Trigger Adjustments

A. Screw ① is the pull weight adjustment screw. Turn this screw clock-wise to increase the pull weight and counter-clockwise to reduce the pull weight.

B. Screw ② is the sear engagement adjustment screw. *This screw is set to the optimum setting during testing at the factory, so it shouldn't be necessary to change it, if you feel that you need to make an adjustment please call the factory first.*

As a service to you, Timney Mfg., Inc. will install your Timney® trigger for \$25.00 plus shipping and handling.

TIMNEY® ADJUSTABLE TRIGGER GUARANTEE

Material and workmanship: This TIMNEY® trigger has been carefully designed, inspected, tested and calibrated to give a lifetime of dependable service. Every possible care has been exercised in its design and construction. If any defect in workmanship or material should develop under conditions of normal use and service, necessary repairs, including parts and labor will be made at no charge to the purchaser, providing that our inspection reveals the trigger was not damaged through accident, alteration, misuse, abuse or other cause beyond our control. We neither assume nor imply any oral or statutory warranties, and we neither assume nor authorize any person to assume us for any obligation or liability in connection with this trigger. Repairs or disassembly of this trigger in any manner without specific factory authorization voids this guarantee.

TIMNEY Mfg., Inc. 3940 W. Clarendon Ave., Phoenix, AZ 85019
602-274-2999 Fax 602-241-0361
service@timneymfg.com www.timneytriggers.com